



Auger – Changing Teeth

Developed by:	Approved by:	Date created:	Last revision:
Jason M. Moffatt	G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present	Personal Protection Required	Additional Training	
<ul style="list-style-type: none"> - Pinch Points - Muscle Strain - Cutting - Injury/amputation 	<ul style="list-style-type: none"> - CSA Footwear - CSA Safety Glasse - Face Shield - Gloves 	<ul style="list-style-type: none"> - PPE 	
<ol style="list-style-type: none"> 1. Wear all applicable PPE. 2. Have operator shut down machine and exit the same. 3. Hammer out old tooth with a sledge hammer, a pin or piece of rebar may be required. 4. Shield yourself while driving in the new tooth. 5. Keep fingers and hands away from kelly bar and areas where they might get jammed. 6. Maintain periodic eye contact with the operator and make sure they are aware when you have completed the task. 			
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>6 - Personal Protective Equipment 16 - Machines, Tools, and Robots 8 - Musculoskeletal Injuries</p>		<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	