



Band Saw

Developed by:		Approved by:		Date created:		Last revision:		
Bill White Safety Coordinator		Jason Moffat		December 2008		December 1, 2022		
Possible Hazards Present			Personal Protection Required			Additional Training		
<ul style="list-style-type: none"> - Exposed blade - Electrical shock - Noise - Sawdust in eyes - Sawdust inhaled 			<ul style="list-style-type: none"> - Eye protection - Hearing protection - Safety footwear - Disposable respirator - Push stick - Guards - Dust collection system 			<ul style="list-style-type: none"> - Material handling - Ergonomics 		
<ol style="list-style-type: none"> 1. Read and understand operators manual. 2. Wear recommended PPE. 3. Ensure the work area is clean and the saw is in good working condition. 4. Inspect the material for defects and foreign objects. 5. Adjust the guard to 1/8th inch above the material height. 6. Ensure all guards are in place. 7. Hold the material firmly and flat and feed steady. Do not force the material. 8. Shut off saw and wait for the blade to stop before removing the material. 9. Lock out the saw and clean up the sawdust. 10. REPORT ANY DANGEROUS SITUATIONS TO THE SUPERVISOR. 								
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>16 - Machine and Tool Safety 6 - Personal Protective Equipment - Operators manual</p>				<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years</p>				