

Crusher Safety – General

	Approved by:	Date created:	Last revision:
Developed by:			
Jason M. Moffatt	G. Kaluzniak	January , 2016	December 1, 2022

Possible Hazards Pres	rds Present Personal Protection Required		F	Additional Training	
Pinch PointsSlipping/FallingWrenches Slipp		 CSA Footwear Safety Vests Hard Hats Hearing Protection Hand Protection 		Crusher Operation Lockout Procedure	

- 1. Document the daily inspection of the equipment on supplied paperwork.
- 2. The safety of persons involved in setup operation/maintaining the equipment can be affected by many factors.
- A. The Location and configuration of the equipment.
- B. The type of equipment being used.
- C. The attachment of additional or optional equipment.
- D. Alteration or modifications.
- E. The type of material being processed.
- F. Operation of equipment by unqualified personal.
- 3. Based on these factors, additional guarding or other precautions may be necessary to comply with the rules and regulations.
- 4. Mount and dismount the equipment using steps, ladders, handrails, and walkways. Use the 3-point contact rule.
- 5. Be aware of your actions and actions of other people and equipment on the jobsite at all times.
- 6. Shut down and lockout power source before opening electrical cabinets, or preforming service, or general maintenance.

Documentation/Legislation Workplace Safety and Health R

Workplace Safety and Health Regulation, M.R. 217/2006

- 2 Safe Work Procedure
- 6 Personal Protective Equipment
- 12 Hearing Conservation & Noise Control
- 16 Machines, Tools & Robots
- 22 Powered Mobile Equipment

This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.