



Diesel Fuel

Developed by:	Approved by:	Date created:	Last revision:
Jason M. Moffatt	G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present	Personal Protection Required	Additional Training	
<ul style="list-style-type: none"> - Toxic Vapours - Flammable 	<ul style="list-style-type: none"> - Gloves - CSA Footwear 	<ul style="list-style-type: none"> - PPE - WHMIS 	
<ol style="list-style-type: none"> 1. Fill Tanks in well vented areas outside. 2. Store all decanted diesel outdoors. 3. Label all decanted containers as per WHMIS. 4. Extinguish all flames, sparks, cigarettes. Do not use cell phones. 5. Turn off engine before filling equipment or slip tanks. 6. Use Genuine spill proof gas containers to transport fuel. 7. Wash hands thoroughly after handling. 8. Avoid inhaling fumes. 9. Clean up spills immediately using spill kit. 			
Documentation/Legislation 4 - General Workplace Requirements 5 - First Aid 6 - Personal Protective Equipment 35 - W.H.M.I.S. - Requirement, Labelling, MSDS 36 - Chemical & Biological Substances		This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.	