



Fall Protection

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> - Falls - Inadequate anchor point, minimum - 5000 lbs rating - Defective equipment - Inadequate training - Hanging in harness after a fall - Equipment Failure 		<ul style="list-style-type: none"> - Proper fall protection must be worn - CSA approved helmet - CSA approved footwear 		<ul style="list-style-type: none"> - Fall Protection - Proper Guardrail Erection
<ol style="list-style-type: none"> 1. Perform a hazard assessment of the job. 2. Determine what equipment will be needed (fall arrest, fall restrain, nets, guardrails) 3. Read and understand manufacturers instructions. 4. Inspect all equipment or guard rails before use. 5. Tag out and remove defective equipment from use. 6. Don equipment and inspect for proper fit as per training or as advised by competent worker. 7. Set up safety lines and anchor points as required before commencing work. 8. Hook to safety line. 9. Ensure retractors and rope grabs are working properly. 10. Be aware of all open edges in your working area. 11. When finished task, leave the danger area and unhook from the safety line. 12. When finished store the equipment in a dry, ventilated area. Hang harnesses. 				
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>14 Fall Protection 28 Scaffolds and Other Elevated Work Platforms 31 Roof Work</p>			<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	