



Fueling Vehicles

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> - Eye injury - Fire/explosion hazards - Burns 		<ul style="list-style-type: none"> - Steel toed boots - Safety vest - Hand protection - Eye protection 		- PPE
<ol style="list-style-type: none"> 1. Bring vehicle to pump or pump to vehicle. 2. Shut off ignition, extinguish any smoking material, leave cell phone in vehicle. 3. Remove fill cap. 4. Insert nozzle into tank and flip lever to on position. 5. Fill until click is heard or to desired amount, then turn lever to off position. 6. Place nozzle back on holder and replace filler cap. <p>***Stay at the station while fueling. The safety mechanism might not work during fueling and therefore create the risk of spillage***</p>				
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>6 Personal Protective Equipment 19 Fire and Explosive Hazards. 35 Workplace Hazardous Materials Information Systems</p>			<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	