



Gasoline

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> - Toxic vapors - Flammable 		<ul style="list-style-type: none"> - Gloves - Steel Toed Boots - Fire Extinguisher 		- WHMIS
<ol style="list-style-type: none"> 1. Fill tanks in well ventilated area or outside. 2. Store all decanted gasoline outdoors. 3. Label all decanted containers as per WHMIS. 4. Extinguish all flames, sparks and cigarettes. Do not use cell phone. 5. Turn off engine before filling equipment or slip tanks. 6. Use genuine spill proof gas containers 7. Wash hands thoroughly after handling 8. Avoid inhaling fumes 9. Clean up spills immediately using a spill kit. 				
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>4 - General Workplace Requirements 5 - First Aid 6 - Personal Protective Equipment 35 - W.H.M.I.S. - Requirement, Labelling, MSDS 36 - Chemical & Biological Substances</p>			<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	