Group of Companies

Granular - Unloading from End Dump

Developed by:	Approved by:		Date created:		Last revision:
Jason M. Moffatt	G. Kaluzniak		January , 2016		December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training	
- Burns - Shock - Electrocution		 Steel Toed Boots Hard Hat Safety Vest 		- Operator Certificate	

1. At dump site check for potential hazards in the dumping area before initiating the backing procedure. Adhere to all posted and printed workplace safety standards to prevent any work-related incidents. Find a spot that is level and stable, (be aware of soft spots where tires may sink).

2. Where required, a spotter will be provided to assist you in backing up. No backing up to proceed until all personnel and equipment are clear of the safe approach limits.

3. Check for any overhead lines in the path of the raised box.

4. Park and ensure brake is applied.

5. Exit cab using 3-point contact.

6. Roll up tarp and secure.

7. Trip the tail gate and ensure that it opens.

8. Engage PTO and pump.

9. Dump airbags & release park brake.

10. Raise box slowly making sure that the trailer is going straight up (watch at all times/remain in truck).

11. If trailer is going up on too much of a slant lower box immediately and find a more level location.

12. Check to make sure all materials are out of the box.

13. When load is dumped slowly drive ahead a few feet and lower hoist. Do not drive any further than necessary while box is still raised.

14. Disengage pump and PTO and close the tailgate.

*Safe operation of a dump truck requires training, experience, and vigilance.

Documentation/Legislation	
Workplace Safety and Health Regulation,	
M.R. 217/2006	This Safe Work Procedure will be
	reviewed anytime the task, equipment
2.1 Safe Work Procedures	or materials change and at a minimum
4 General Workplace Requirements	every three years.
16 Machines, Tools and Robots	
22 Powered Mobile Equipment	