



### Masonry Saw - Dry Cutting

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> <li>- Pinch Points</li> <li>- Cuts</li> <li>- Electrical</li> <li>- Silica Dust</li> </ul>		<ul style="list-style-type: none"> <li>- CSA Footwear</li> <li>- CSA Safety Glasses</li> <li>- Respiratory Protection</li> </ul>		<ul style="list-style-type: none"> <li>- PPE</li> <li>- Fit test</li> </ul>
<ol style="list-style-type: none"> <li>1. Use a proper blade, which is marked for dry cutting.</li> <li>2. Remove the water curtain.</li> <li>3. Disconnect the water pump.</li> <li>4. Use step cutting when using dry cutting diamond blades.</li> <li>5. Use jam or step cutting when using dry cutting diamond blades.</li> </ol>				
<p><b>Documentation/Legislation</b>                  Workplace Safety and Health Regulation,                  M.R. 217/2006</p> <p>6.15 Respiratory Protective Equipment                  6 - Personal Protective Equipment                  16 - Machines, Tools, &amp; Robots</p>			<p><b>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</b></p>	