

## **Mixer - Operating from Rear**

	Approved by:	Date created:	Last revision:
Developed by:			
Jason M. Moffatt	G. Kaluzniak	January , 2016	December 1, 2022

Possible Hazards Present	Personal Protection Required	Additional Training
<ul><li>Pinch Points</li><li>Splashing concrete</li><li>Slip/fall hazard</li><li>Excessive noise</li></ul>	<ul> <li>CSA Footwear</li> <li>CSA Safety Glasses</li> <li>CSA Hard Hat</li> <li>CSA Hearing Protection Gloves High Visibility Vest </li> </ul>	- PPE

- 1. If pouring directly, no mixer will be within a distance equal to the depth of any excavation.
- 2. Mount, swing, and align chutes appropriate to job-site application.
- 3. Do Not attach job-built chutes to truck's chutes.
- 4. Ensure that area below ladder, rungs, and rear platform are free and clear of mud, ice, snow, etc.
- 5. Maintain 3-point contact and face truck when climbing up and down ladder to access rear pedestal. NEVER jump down from rear of mixer truck.
- 6. Slow mixing drum down to reduce splashing concrete, check slump.
- 7. Change drum rotation from mixer to discharge.
- 8. Unload concrete at appropriate speed, maintaining contact with pump operator/contractor.
- 9. Concrete splashed on bare skin requires immediate rinsing with water.
- 10. Beware of pinch points around ladder hinges, chute swivels, flip chute, fill hopper, drum rollers and turning drum.
- 11. NEVER attempt to reach into turning drum, area between turning drum and chute and/or drum rollers. These are critical pinch points requiring extreme caution.
- 12. Beware of loose clothing when climbing up or down from rear platform and near drum and rollers.
- 13. As important as it is to be aware of your surroundings, the priority focus should be the safe operation of the mixer. Distractions can lead to serious consequences.

## Documentation/Legislation

Workplace Safety and Health Regulation, M.R. 217/2006

6 Personal Protective Equipment 22 Powered Mobile Equipment This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.