



### Propane Heaters

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> <li>- Fumes/Exhaust</li> <li>- Flammable materials</li> <li>- Tripping hazard</li> </ul>		<ul style="list-style-type: none"> <li>- Steel Toed Boots</li> <li>- Hard Hat</li> <li>- Safety Vest</li> <li>- Hand Protection</li> </ul>		
<ol style="list-style-type: none"> <li>1. Flammable materials (including propane bottle) is to be located a minimum of 50 feet from the front of the heater.</li> <li>2. All flammable materials (including propane bottle) is to be located a minimum of 10 feet from the sides, rear and top of the heater.</li> <li>3. The heater hose length should not be more than 50 feet.</li> <li>4. Extra hose is to be coiled and tied so that it is not a tripping hazard.</li> <li>5. Hose lying on the floor or ground in traffic areas should be protected against puncture.</li> <li>6. Propane tanks must be stored in a well-ventilated and safe, secure place to prevent tipping or any other damage.</li> <li>7. Ensure there is sufficient space for the exhaust and ventilation of the heater.</li> </ol>				
<p><b>Documentation/Legislation</b>                  Workplace Safety and Health Regulation,                  M.R. 217/2006</p> <p>16 Machines, Tools and Robots                  4.1 General Workplace Requirements</p>			<p><b>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</b></p>	