

Skid Steer Operator

	Approved by:	Date created:	Last revision:
Developed by:			
Jason M. Moffatt	G. Kaluzniak	January , 2016	December 1, 2022
Describe Harring Discount Description		\t. = 4	delitional Training

Possible Hazards Present	Personal Protection Required	Additional Training
 Vehicle or property damage Serious injury Pinch points Other workers Slips/trips 	Steel toed bootsHard HatSafety Vest	- PPE - Skid Steer Operator

- 1. Before work begins, discuss job to be done with all involved.
- 2. Secure the work area and survey for hazards.
- 3. Perform pre-trip inspection and record in log.
- 4. Enter machine using 3-point contact method and start.
- 5. Check back up alarm, all gauges, brakes and hydraulics.
- 6. Wear the seat belt and have the seat bar lowered at all times.
- 7. Turn on the beacon light.
- 8. In tight areas or where traffic is heavy use a spotter.
- 9. Load only what the skid steer can handle.
- 10. Always carry the bucket as low as possible.
- 11.Load, unload and turn on float, level ground.
- 12.Be aware of all people and obstructions in the operating area at all times.
- 13. When job is done park on level ground with attachments resting on the ground.
- 14. Park and secure machine.
- 15. Turn machine off.
- 16. When finished operation for the day turn the Master Ignition Switch to the OFF position.
- 16.Exit machine using 3-point contact.

Documentation/Legislation

Workplace Safety and Health Regulation, M.R. 217/2006

- 6 Personal Protective Equipment
- 16 Machines, Tools and Robots
- 20 Vehicular and Pedestrian Traffic
- 22 Powered Mobile Equipment

This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.