



Wheeled Loader- Loading/Unloading

Developed by:	Approved by:	Date created:	Last revision:
Jason M. Moffatt	G. Kaluzniak	November 27, 2008	December 1, 2022
Possible Hazards Present	Personal Protection Required	Additional Training	
<ul style="list-style-type: none"> - Slip/Trip hazard - Fall Injury - Vehicle/Machine damage - Pinch Points 	<ul style="list-style-type: none"> - Steel Toed Boots - Hard Hat - Safety Vest 	<ul style="list-style-type: none"> - Operator Certificate 	
<p>Loading</p> <ol style="list-style-type: none"> 1. Enter loader using 3 point contact method. 2. Drive up to back of trailer, making sure you are straight and properly aligned. 3. Keep bucket about 6" from trailer bed. 4. Gradually and cautiously drive onto trailer until bucket is at front of trailer. 5. Lower bucket, and set brakes. 6. Exit cab using 3-point contact method. 7. Dismount trailer by sitting on deck and pushing yourself off. 8. Secure load with chains and stabilizer bar. 9. Inspect load and proceed to destination. <p>Unloading</p> <ol style="list-style-type: none"> 10. Park truck on level ground and set brake. 11. Exit cab using 3-point contact. 12. Remove chains and stabilizer bar. 13. Set up ramps. 14. Mount loader using 3-point contact. Release brake and raise bucket to a low level. 15. Back up slowly and cautiously till loader is on the ground. 16. Inspect jobsite for hazards, and you are ready for work. 17. When finished operation for the day turn the Master Ignition Switch to the OFF position. 			
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>4 General Workplace Requirements 6 Personal Protective Equipment 16 Machines, Tools and Robots 22 Powered Mobile Equipment</p>		<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	