



Working Under Vehicles

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January , 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> - Muscle strain - Serious injury - Pinch points/crushing 		<ul style="list-style-type: none"> - Steel toed boots - Hand protection 		- PPE
<ol style="list-style-type: none"> 1. Park vehicle/machine on level ground free of debris. 2. Lock out machine/vehicle. 3. Ensure all tools are on hand. 4. Ensure applicable brakes are applied. 5. Place blocks behind wheels. 4. Hoist vehicle using proper method. 5. Place supports such as: <ol style="list-style-type: none"> A. Vehicle Support Stands B. Wood Fabricated Stands C. Automotive Hoists 6. Cautiously proceed under the vehicle using a creeper if possible. 7. Perform work. 8. Clean up area when finished. 9. Remove supports and lower vehicle/machine. 				
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>6 Personal Protective Equipment 8 Musculoskeletal Injuries</p>			<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	