



Yard Trailer Loading

Developed by:		Approved by:	Date created:	Last revision:
Jason M. Moffatt		G. Kaluzniak	January, 2016	December 1, 2022
Possible Hazards Present		Personal Protection Required		Additional Training
<ul style="list-style-type: none"> - Load stability & securement - Overloading - Equipment failure 		<ul style="list-style-type: none"> - CSA Footwear - High Visibility Clothing 		<ul style="list-style-type: none"> - PPE - Lift truck Certificate
<ol style="list-style-type: none"> 1. Perform pre-trip inspection of deck trailer including but not exclusive to the hitch, safety chains, lights, tires, jack, side rails, trailer deck, etc. 2. Inspect pallet or unit to be loaded to ensure material is secure and stable. 3. Establish weight of each unit to be loaded (estimate or actual). 4. Load trailer with heaviest pallets or material over or slightly forward of the front axle of the trailer. 5. Follow with equivalent weight or as close as possible over or slightly behind the rear axle of the trailer. 6. Load front of trailer with next lightest material. 7. Load rear of trailer with lightest material. 8. Secure with appropriate load straps. 				
<p>Documentation/Legislation Workplace Safety and Health Regulation, M.R. 217/2006</p> <p>6 Personal Protective Equipment 22(28-30) - Powered Lift Trucks</p>			<p>This Safe Work Procedure will be reviewed anytime the task, equipment or materials change and at a minimum every three years.</p>	